


02P~03P




P/N LEGEND

A2501 HB-XP N 0 W NP N 00 G
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩



- ① Series No.
- ② Connector type: HB=Housing B type
- ③ No. of circuits
- ④ N=Halogen Free
- ⑤ Material: 0=Nylon 66-V0
- ⑥ Color: W=White
- ⑦ Plating code: NP=Non-plating
- ⑧ Plating code: N=Non-plating
- ⑨ Option code: 00=Standard
- ⑩ Packing code: G=Bag

SPECIFICATIONS

Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 10mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1000V AC/minute
Material: Nylon 66,UL94V-0
Color: Natural(White)



Circuit No.	Dimensions			
	A	B	C	D
02P	2.50	5.70	7.20	3.00
03P	5.00	8.20	9.70	3.00
04P	7.50	10.70	12.20	5.30
05P	10.00	13.20	14.70	6.50
06P	12.50	15.70	17.20	6.50
07P	15.00	18.20	19.70	10.30
08P	17.50	20.70	22.20	10.30
09P	20.00	23.20	24.70	10.30
10P	22.50	25.70	27.20	15.30
11P	25.00	28.20	29.70	15.30
12P	27.50	30.70	32.20	15.30
13P	30.00	33.20	34.70	15.30
14P	32.50	35.70	37.20	15.30
15P	35.00	38.20	39.70	15.30

					燦達電子工業股份有限公司			
					JOINT TECH ELECTRONIC IND. CO., LTD.			
					UNIT	SCALE	SHEET	TITLE: 2.50mm PITCH HOUSING
					mm	1 : 1	1 of 1	
				DRAWN BY		APPROVED BY		
				周傑亮		陳彥兆		
				2013.11.06		2013.11.06		
				GENERAL TOLERANCE				
A1	EN1410240001	2014.10.24	周傑亮	X. X±0.25		ANGLE±	DRAW NO. : A2501HB-XPNXXXXXXXXX	REV. A1
A0	NEW RELEASE	2014.1.16	周傑亮	X. XX±0.15				
REV.	DESCRIPTION	DATE	NAME	X. XXX±0.05				